

## HIGH TRANSMITTANCE ALUMINA FOR CERAMIC METAL HALIDE LAMPS

### BACKGROUND OF THE INVENTION

The present invention relates to high transmittance alumina arc tubes for use in electric lamps. It finds particular application in conjunction with ceramic metal halide arc tubes, and will be described with particular reference thereto. It should be appreciated, however, that the invention is also applicable to other lamp envelopes and shrouds for lamps where high transmittance is desired.

Metal halide lamps have conventionally been constructed of a fused silica (quartz) arc tube containing a fill of a light-emitting metal, such as sodium, commonly in the form of the halide, and optionally mercury. The lifetime of such lamps is often limited by the loss of the metal portion of the metal halide fill during lamp operation due to metal ion diffusion, or reaction of the metal halide with the fused silica arc tube, and a corresponding build-up of free halogen in the arc tube.

Recently, ceramic metal halide lamps having polycrystalline alumina arc tubes have been developed which provide advantages over quartz arc tubes. U.S. Patent Nos. 5,424,609; 5,698,948; and 5,751,111 provide examples of such arc tubes. Ceramic alumina arc tubes are less permeable to sodium ions than quartz and thus retain the metal within the lamp. They are also able to withstand much higher operating temperatures than quartz arc tubes. While quartz arc tubes are limited to operating temperatures of around 900-1000°C, due to reaction of the halide fill with the glass, ceramic alumina arc tubes are capable of withstanding operating temperatures of 1100 to 1200°C, or higher. The higher operating temperatures provide better color rendering and higher lamp efficiency.

LD 10807

Alumina arc tubes are generally constructed of a number of separate parts. The parts are extruded or die pressed from a ceramic powder mixed with an organic binder. European patent Application No. 0 587 238 A1, for example, discloses a ceramic discharge tube of translucent aluminum oxide. Typically, the parts are tacked together with an adhesive and then sintered to form gas-tight monolithic joints between the components.

Another potential arc tube material for metal halide lamps is sapphire. Sapphire arc tubes have been found to provide improved lamp performances over alumina arc tubes due to increased transmission levels. However, such lamps are expensive due to the cost of manufacturing the monocrystalline sapphire material. There are also problems in sealing of the lamps to prevent loss of the fill material.

Improvements in the transmittance of polycrystalline alumina arc tubes have been found when the arc tubes are chemically polished with an alkali metal borate composition. U.S. Patent Nos. 4,033, 743, and 4,633,137 to Scott, et al. disclose a method of contacting an arc tube body with a molten inorganic borate flux which preferentially dissolves a surface layer of alumina grains. The process does not, however, provide arc tubes with transmittances comparable to sapphire because of microscopic discontinuities, or porous regions, in the arc tube surface. The discontinuities remain, even after polishing, reducing the transmittance of the arc tube.

The present invention provides for an improved ceramic body, such as a metal halide arc tube and method of preparation, which has optical performance characteristics approaching those of sapphire.

LD 10807

## SUMMARY OF THE INVENTION

In an exemplary embodiment of the present invention, a method of providing a translucent ceramic body with increased in-line optical transmission is provided. The method includes densifying a ceramic body to form a substantially translucent ceramic body. The densifying process includes heating the ceramic body under a pressure of at least 350 kg/sq.cm . The method further includes physically contacting a major surface of the substantially translucent ceramic body with a molten inorganic flux at elevated temperatures and for a time period sufficient to improve transmittance of the ceramic body. The flux includes an alkali metal borate capable of dissolving the ceramic.

In another exemplary embodiment, an optically transparent densified, sintered polycrystalline ceramic body is provided. The body has a major surface which has been treated with a process which includes heating a ceramic body in an inert atmosphere a pressure of at least 350 kg/sq.cm for a sufficient time to form a substantially translucent polycrystalline ceramic body. The process further includes physically contacting a major surface of the substantially translucent ceramic body with a molten inorganic flux which includes an alkali metal borate capable of dissolving the ceramic at elevated temperatures and for a time period sufficient to improve light transmittance by the ceramic body.

In another exemplary embodiment, a high intensity electric discharge lamp is provided. The lamp includes a discharge vessel which defines a chamber. The discharge vessel is constructed from a polycrystalline material which has been densified by applying sufficient pressure and temperature to reduce pores in the vessel and polished by physically contacting a major surface of the substantially translucent vessel with a molten inorganic flux at

LD 10807

an elevated temperature and for a time period sufficient to reduce unevenness in the major surface. The lamp further includes electrodes sealed into ends of the chamber and a fill sealed within the chamber. The fill includes a ionizable medium for initiating and sustaining a discharge.

5

One advantage of the present invention is that it enables an alumina arc tube with high transmittance to be formed.

Another advantage of the present invention which derives from the ability of the arc tube to transmit light with minimal scattering from the smooth surface and allows for lamps formed from the material to provide a more point source illumination.

Still further advantages of the present invention will become apparent to those of ordinary skill in the art upon reading and understanding the following detailed description of the preferred embodiments.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a side view of a high transmission metal halide lamp according to the present invention;

FIGURE 2 is a side view of an unassembled ceramic arc tube according to the present invention;

FIGURE 3 is an side view of a partially assembled ceramic arc tube according to the present invention;

FIGURE 4 is a side view of the ceramic arc tube of FIGURE 1; and

FIGURE 5 is a plot of luminous flux through an aperture versus aperture size for unpolished and polished lamps.

25

LD 10807

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to FIGURES 1-3, a, high-pressure metal halide lamp is provided with a discharge vessel 1, including a high-transmission arc tube or body 10 which encloses a chamber or discharge space 12. The arc tube has its major surfaces physically and chemically treated to provide increased optical transmission in a manner which will be more fully explained hereinafter.

The discharge space preferably contains a fill which comprises at least one metal halide, such as sodium iodide, thallium iodide or dysprosium iodide, in addition to mercury and a rare gas, such as Argon or Xenon. Other suitable fills, for initiating and sustaining an arc discharge, known in the art, are also contemplated. The discharge vessel is enclosed in an outer envelope 14, which is provided with a lamp cap 16 at one end.

First and second internal electrodes 20, 22 extend into the discharge space 12. The electrodes are formed from tungsten, or other known electrode materials. A discharge forms between the electrodes when the lamp is in an operational state. Current conductors 24 and 26 connect the electrodes 20 and 22, respectively, to first and second electrical contact forming parts of the cap 16. In a preferred embodiment, the current conductors each comprise a niobium lead-in portion 27 welded to a molybdenum portion 28 which, in turn, is welded to the respective tungsten electrode. The molybdenum portion may have an overwind of molybdenum (see FIGURE 4).

With particular reference to FIGURES 2 and 3, the ceramic arc tube 10 (not to scale) comprises an outer wall 30, which includes a cylindrical portion 32 with end wall portions 34 and 36 at either end, although other arc tube shapes are also contemplated. Each of the end wall portions defines an opening 38, 40. First and second tubes 42, 44 extend outwardly from the end wall portions 34 and 36, respectively, and are connected to the end walls

LD 10807

around the openings. The current conductors 24 and 26 are received by the first and second tubes. The conductors are sealed into the tubes with seals 46 and 48 to create a gas-tight discharge space.

5 The cylindrical portion, end wall portions and also the first and second tubes are preferably all formed from a polycrystalline aluminum oxide ceramic, although other polycrystalline ceramic materials capable of withstanding high wall temperatures up to 1700-1900°C and resistant to attack by the fill materials are also contemplated.

10  
15  
20  
25

As shown in FIGURES 2-4, the arc tube 10 is readily assembled from separate components, each component corresponding to one of the first and second tubes, end wall portions, and cylindrical portions.

The components are fabricated by die pressing or extruding a mixture of a ceramic powder and an organic binder. The components are pre-sintered to about 900-1200°C in air to remove the organic processing aids. Assembly of the arc tube involves placement and tacking of the components. With particular reference to FIGURE 3, the first and second tubes are similarly tacked to the respective end portions with an adhesive and the end portions are tacked to the cylindrical portion. The tacked components are then partially sintered at a temperature of around 1500-1850°C in H<sub>2</sub> to form gas-tight joints. During this sintering, the components shrink to different extents.

The differential shrinkage is used advantageously in forming the gas-tight joints. The step of heating in H<sub>2</sub> also increases the density of the ceramic material and reduces the porosity but nevertheless leaves the ceramic with some porosity which affects transmission. Alternatively, the arc tube may be formed with fewer or more components. U.S. Patent Nos. 5,424,609, 5,698,948, and 5,751,111 disclose alternative arc tube bodies which may be used.

The partially sintered Al<sub>2</sub> O<sub>3</sub> arc tube has a few percent of "closed" porosity, i.e. pores within the arc tube which are not open to the

LD 10807

atmosphere, and few, if any, "open" pores. At this stage, the tube is about 90% or more of its final density. The closed pores are typically located at the grain boundaries. The tube preferably has an alumina content of about 99.99%, with magnesia (MgO) present at up to 0.5 weight percent, and preferably at about 400-1500 ppm. The magnesia imparts transparency to the finished tube and ensures that most pores remain on the grain boundaries during sintering. Alternatively, other transparent ceramic oxides, such as  $Y_2O_3$ , yttrium aluminate, or mullite ( $Al_2O_3-2SiO_2$ ) may be used in place of alumina, or a combination of ceramic oxides may be employed.

To form a high-transmittance arc tube, the sintered arc tube is subjected to a two-step process. The first step includes a densifying and/or porosity reducing step process, such as hot isostatic pressing of the arc tube. The second step includes chemically polishing the surface of the tube.

In the first step, the alumina arc tube is heated in an inert atmosphere at a temperature of from about 1600 to 1900°C at a pressure of about 5000 psi (350 kg/sq.cm.), or greater, more preferably, from about 10,000 to 30,000 psi (700-2100 kg/sq.cm.) for a period of from about one to about three hours. The pressure is preferably held relatively constant (isostatic) during the densifying process. While pressures of around 5000 psi (350 kg/sq.cm.) can reduce porosity, higher pressures are more effective in pore elimination. High pressures are also beneficial if there is residual pressure inside the pores being hot isostatically pressed.

Argon gas provides a suitable inert atmosphere, although other inert gases are also contemplated. The sintered ceramic is converted to a semi-transparent polycrystalline aluminum oxide. The pressure eliminates substantially all microscopic porosity which otherwise would reduce the effectiveness of the second, polishing step. The hot isostatic pressing step also strengthens the joints between the components of the arc tube.

LD 10807

During hot isostatic pressing, pores of diameter less than about 5 microns are significantly reduced or eliminated.

Although hot isostatic pressing is a preferred final densifying process, other methods of converting the dense arc tube body unto a translucent ceramic are also contemplated. For example, it is contemplated that the green or partially sintered ceramic body may be contained so that it can be isostatically pressed to translucency in a single step.

In the second step, the outer surface 50 of the arc tube 10 is physically contacted with molten in organic flux that dissolves alumina at a moderate rate until a surface layer has been dissolved to provide a relatively smooth appearance. About 50 microns may be dissolved in this step. It is preferably in carrying out this type of chemical polishing treatment that the flux composition also be selected so as to dissolve the surface layer of the alumina grains preferentially, rather than dissolve any material at the grain boundaries. This provides a surface flattening action. The preferred fluxing agents should also remain stable in the molten condition at elevated temperatures of treatment of up to around 1000°C.

Useful fluxing agents for providing a relatively smooth and flat surface in the foregoing manner are those which do not tend to produce insoluble reaction products at the molten liquid interface which hinder the dissolving process or form an optical scattering surface having poor in-line transmission. The alkali metal borates provide a general class of useful flux compositions demonstrating the above-mentioned thermal and chemical stability in a molten state. Preferred fluxing agents from this class are those which are readily removed from the polished surfaces by dissolution in a weak acid or other suitable washing process. In particular, sodium and potassium borates, alone or in combination, provide good fluxing agents. Borates of the general form  $(M_2O)_n (B_2O_3)_m$ , where M is Na, K, or a mixture



LD 10807

of both, and n and m are integers with the ratio of n to m being in the range of from 1:2 to 1:4 are particularly preferred.

5 The fluxing medium may also contain, in addition to one or more of the borates, a small amount of an alkali metal chloride, such as NaCl or KCl. The chloride is preferably present at a concentration of from about 5-25% and improves removal of the flux after polishing.

To polish the arc tube, it is preferable to carry out the dissolving action in an oxygen containing atmosphere, such as air. In one method, the arc tube is immersed in the molten alkali metal borate or other fluxing agent at moderately elevated temperatures not exceeding approximately 1000°C.

10 This avoids excessive volatilization of the fluxing agent, although the arc tube is capable of withstanding more elevated temperatures if desired. To minimize thermal shock when the treated member is first removed from the molten flux bath it is preferable to return the arc tube to ambient temperature by controlled cooling of the tube, in conventional fashion.

15 Alkali metal borate fluxes leave a glassy coating on the treated alumina arc tube, which should be removed for optimum in-line transmission. The coating can be dissolved by washing the treated arc tube in a dilute, heated acid solution after it has been cooled.

20 Alternatively, a glaze polishing method can be used to reduce the surface irregularities. Rather than immersing the arc tube in the molten flux, the flux is produced by coating the arc tube with flux forming materials and then heating to a sufficient temperature to form a flux from the coating. In this method, an alkali borate glass frit can be ground or otherwise formed  
25 into a fine powder and formed into a suspension with a suitable carrier liquid, such as methanol. The alkali metal borate is preferably a borate other than lithium borate, with an alkali metal oxide to boron oxide weight ratio in the range of from 1:2 to about 1:4. The frit suspension is applied to the arc tube surface, such as by painting, and then dried to remove all or most of the

LD 10807

carrier. The arc tube can then be heated to a sufficient temperature to melt the glazing material, preferably between about 800°C and 1025 C, for a period of from about 1-2 hours, thereby glazing and polishing the surface.

In one exemplary glaze polishing method, borax, boric oxide, sodium carbonate, and potassium carbonate are mixed. and then heated until melting. The glass material produced is poured into water to produce a frit.

The frit is then ground, passed through a screen, and mixed with a carrier, such as a lower alcohol, e.g., methanol or isopropanol. The suspension may further comprise a binder, such as polyvinyl pyrrolidone, and a dispersant, such as glycerol trioleate. The suspension is deposited on an unpolished alumina arc tube and allowed to dry under ambient conditions. The coated alumina tube is then heated to a temperature of between 875°C and 1025°C for 30 minutes to 2 hours to melt the coating and create a flux similar to that formed when a bath of molten flux is used and thereby remove a portion of the underlying alumina surface. The polishing residue is then removed by washing the treated tube in a heated dilute aqueous HCl solution. The surface produced, like that produced by flux polishing, is of a generally flat nature, the polishing process having removed high spots on the individual alumina grains without introducing significant low spots at the grain boundaries.

The polished high transmittance ceramic arc tubes produced in this manner show improved optical transmission over conventional polycrystalline alumina arc tubes. Ceramic metal halide lamps fabricated with the high transmittance ceramic tubes have transmittances approaching those of sapphire arc tube lamps and much superior to those of conventional, polycrystalline alumina lamps.

Without intending to limit the scope of the invention, the following examples show how the polished metal halide lamp compares with conventional metal halide lamps and arc stream lamps.

LD 10807

## EXAMPLES

## EXAMPLE 1

## Hot Isostatic Pressing of Alumina Arc Tubes

5

Sintered, dense 150 watt ceramic metal halide arc tubes of Lucalox™ were placed into a molybdenum crucible. The crucible was placed into a Conway hot isostatic press and argon introduced at 1000 psi (70 kg/sq.cm.).

The arc tubes were heated to about 1750°C at a heating rate of 12.5°C/min, at which time the pressure was 24,500 psi (1722 kg/sq.cm.), and held at a pressure of about 24,500 psi for 1 hour. After pressing, it was observed that pores of about 5 μ or less were significantly reduced or eliminated. While Lucalox begins showing plasticity or creep at about 1400°C, temperatures in excess of 1600°C are particularly suited for decreasing porosity.

## EXAMPLE 2

## Comparison of Chemically Polished with Unpolished Lamps

20

Three types of ceramic metal halide lamps (CMH 7009, 700B, and 7001) were prepared. Some of the lamps had arc tubes which were polished by a glaze polishing process, others were left unpolished. The arc tubes for each lamp were first hot isostatically pressed in a heated pressure vessel, as described in Example 1. Then, those arc tubes which were to be polished were glaze polished by coating the arc tube with a suspension of sodium and potassium borate  $[(K_2O)(Na_2O)(B_2O_3)_6]$  in methanol. The coated arc tubes were heated to a temperature of about 900°C. This temperature was above the melting point of the glass coating, which was about 850°C, and also above the melting point of the glass coating when some of the alumina has dissolved in the molten glass, which was somewhat higher. The polishing residue is then removed by washing the treated tube in a heated dilute aqueous HCl solution.

25

30

LD 10807

The effect of chemical polishing was clearly evident by comparing photographs of the projected image from the polished and unpolished arctubes in lamps. The unpolished arctube, in the operating lamp, appears bright white with no resolved features, while the lamp with the ceramic tube that had been pressed and chemically polished showed the visible plasma.

#### 1) Total lumen measurements.

The total output of chemically polished CMH lamps was compared with that of an Arc stream™ lamp ( a quartz metal halide lamp manufactured in Europe by General Electric) and a non-polished CMH lamp in a large integrating sphere. The large sphere was calibrated using a three fiber XMH-60 source. Lumen measurements were taken from all three fibers using the Graseby optronics 371 integrating sphere. The fibers were then measured individually and simultaneously to ensure the detector in the large sphere was operating within its linear region for the lamp measurements. The detector was read using an ammeter and the calibration factor found using the fiber source. The non-polished CMH lamp and the Arcstream lamp were run at 120.0 VAC, while the voltage of the chemically polished CMH lamps was varied so that they ran at the same total wattage output as the non-polished CMH lamps. The total lumen output for the pressed and polished CMH lamps was greater than for the controls.

#### 2) Aperture measurements.

All of the lamps tested were placed in turn in a GE MR20-B1 reflector. The Graseby 371 integrating sphere was placed at the focus of the reflector and the lamp position and sphere position were maximized using the CMH 7001 lamp with a 9mm aperture on the sphere. The non-polished CMH and the Arcstream lamp were run at a 120.0VAC and the polished CMH lamps were run at the same voltages as for the large sphere measurements.

LD 10807

Lumen measurements were taken with 6, 9, 12, and 17.5mm apertures. The results are shown in TABLE 1.

TABLE 1

Aperture Size (mm)	Arcstream Luminous Flux	Old CMH Luminous Flux	Chem pol CMH 7009 Luminous Flux	Chem pol CMH 700B Luminous Flux	Chem pol CMH 7001 Luminous Flux
0	0	0	0	0	0
6	885	587	691	718	680
9	1174	806	922	892	912
12	1571	1070	1174	1259	1058
17.5	2672	1942	2160	2136	1974

FIGURE 5 is a plot of luminous flux through an aperture versus aperture size for the five lamp types.

Because the arc length in the CMH lamp is about twice that of the Arcstream lamp, it was not expected that more light would be obtained in a 17.5mm aperture for the polished CMH than for the Arcstream. However, in the best case, 83% of the light from the Arcstream was obtained using the present chemically polished CMH. Comparing the polished CMH and the normal CMH lamps, a 22% increase in the light into a 6mm aperture was obtained for the best lamps. CRI was higher in the polished bulb 85a than in the Arcstream 80. The results suggest that reducing the arc length to about 5mm or less, a CMH lamp could be used for fiber optic applications.

The invention has been described with reference to the preferred embodiment. Obviously, modifications and alterations will occur to others upon reading and understanding the preceding detailed description.

LD 10807

It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000